

SwivelSeal (and SwivelSeal Kit)



Durable exhaust coupling that allows joint serviceability while providing high clamp-load capability.


Angle Adjustable up to 6 Degrees | Low-Weight and Low Leakage Rate | Higher Torsion than Conventional Ball-Shaped Flange Connections

SWIVELSEAL*


Hex-Head Screw with Integrated Washer
All 304 Stainless Steel
Solid Chromium-Free Trunnion Hardware

SWIVELSEAL KIT

One 8" Pipe with Stepped Ball end
One 8" Pipe with mating Flare end
SwivelSeal Exhaust Clamp in 304 Stainless Steel



Units: mm



31.8



SWIVELSEAL*		Nominal Joint Diameter	
Brand PN	Global PN	inches	mm
93-0098	0595 8084 055	2	55
93-0099	0595 8084 060	2 1/4	60
93-0100	0595 8084 065	2 1/2	65
93-0101	0595 8084 070	2 3/4	70
—	0595 8081 075	3	75
93-0097	0595 8902 090	3 1/2	90

*Clamp requires special formed ball and flare pipe ends.

Note: Additional sizes are available to meet specific application requirements.

SWIVELSEAL KIT Global PN	Nominal Joint Diameter	
	inches	mm
0595 7000 065	2 1/2	65
0595 7000 070	2 3/4	70
0595 7000 075	3	75

