

Torca® TorcTite® Exhaust Clamps

Featuring reaction block technology design – invented by Torca – TorcTite exhaust clamps provide a tight, durable 360° seal that won't crush pipes and ruin exhaust flow. Corrosion-resistant stainless steel provides superior strength and is compatible with pipes, flex and mufflers. Available in 3 configurations – butt style, lap style and lap style with gasket.



Fast, Easy & Accurate Installation

- Pre-assembled wideband design easily fits over slip joints to connect exhaust system components
- No need to separate pipes or exhaust members before clamping
- Specific OEM & service designs

Maximum Efficiency

- Ultimate performance under extreme conditions make Torca TorcTite the OEM preferred choice
- Butt style joints allow for easy connection of two same diameter pipes
- Lap style joints allow for connection of overlapping pipes
- Lap style with gasket allows for connection of overlapping pipes and includes a temperature-resistant fiberglass gasket attached to the reaction block for improved leak performance



MADE IN THE
USA



TorcTite® Exhaust Clamps

Durable clamping performance for pipes, exhaust and mufflers.

- Superior clamp load capacity
- Aluminized and 304 stainless steels
- Pre-assembled
- Diameter range: 2" – 6"



TorcTite with Lap Style Joint

Stainless steel with pre-attached hardware and Grade 8 bolts for high strength & temperature durability.



TORCTITE ALUMINIZED LAP STYLE JOINT				TORCTITE 304 SS LAP STYLE JOINT				TORCTITE BRIGHT FINISH LAP STYLE JOINT			
Brand PN	Global PN	inches	mm	Brand PN	Global PN	inches	mm	Brand PN	Global PN	inches	mm
L20AA	0368 0107 051	2	50.8	L20SA	0368 0110 051	2	50.8	L40BA*	0368 0126 102*	4	101.6
L22AA	0368 0103 056	2-1/4	57.2	L22SA	0368 0103 057	2-1/4	57.2	L50BA*	0368 0110 127*	5	127.0
L25AA	0368 0108 064	2-1/2	63.5	L25SA	0368 0113 064	2-1/2	63.5	L60BA*	0368 0121 152*	6	152.4
L27AA	0368 0103 069	2-3/4	69.9	L27SA	0368 0105 070	2-3/4	69.9				
L30AA	0368 0123 076	3	76.2	L30SA	0368 0112 076	3	76.2				
L35AA	0368 0107 089	3-1/2	88.9	L35SA	0368 0110 089	3-1/2	88.9				
L40AA	0368 0133 102	4	101.6	L40SA	0368 0122 102	4	101.6				
L45AA	0368 0115 114	4-1/2	114.3	L45SA	0368 0112 114	4-1/2	114.3				
L50AA	0368 0132 127	5	127.0	L50SA	0368 0113 127	5	127.0				
L60AA	0368 0112 152	6	152.4	L60SA	0368 0110 152	6	152.4				

TorcTite with Lap Style Joint with Gasket

Stainless steel with pre-attached hardware and Grade 8 bolts for high strength & temperature durability.



TORCTITE ALUMINIZED LAP STYLE JOINT				TORCTITE 304 SS LAP STYLE JOINT				TORCTITE BRIGHT FINISH LAP STYLE JOINT			
Brand PN	Global PN	inches	mm	Brand PN	Global PN	inches	mm	Brand PN	Global PN	inches	mm
L30AA-G	0368 0119 076	3	76.2	L30SA-G	0368 0118 076	3	76.2	L35BA-G	0368 0123 089	3-1/2	88.9
L35AA-G	0368 0125 089	3-1/2	88.9	L35SA-G	0368 0124 089	3-1/2	88.9	L40BA-G	0368 0116 102	4	101.6
L40AA-G	0368 0120 102	4	101.6	L40SA-G	0368 0119 102	4	101.6	L50BA-G	0368 0127 127	5	127.0
L50AA-G	0368 0122 127	5	127.0	L50SA-G	0368 0124 127	5	127.0				

TorcTite with Threaded Half Rounds

Aluminized steel with threaded half round replaces the standard nut for easier installation and tightening.



TORCTITE ALUMINIZED THREADED HALF ROUNDS			TORCTITE 304 SS THREADED HALF ROUNDS		
Global PN	inches	mm	Global PN	inches	mm
0368 0109 051	2	50.8	0368 0114 051	2	50.8
0368 0106 056	2-1/4	57.2	0368 0106 057	2-1/4	57.2
0368 0115 064	2-1/2	63.5	0368 0110 064	2-1/2	63.5
0368 0106 069	2-3/4	69.9	0368 0107 070	2-3/4	69.9
0368 0117 076	3	76.2	0368 0114 076	3	76.2
0368 0112 089	3-1/2	88.9	0368 0113 089	3-1/2	88.9
0368 0112 102	4	101.6	0368 0132 102	4	101.6
0368 0116 114	4-1/2	114.3	0368 0109 114	4-1/2	114.3
0368 0123 127	5	127.0	0368 0125 127	5	127.0
0368 0115 152	6	152.4	0368 0108 152	6	152.4

TorcTite with Butt Style Joint

Stainless steel with pre-attached hardware and bolts for for high strength & temperature durability.



TORCTITE ALUMINIZED BUTT STYLE JOINT				TORCTITE 304 SS BUTT STYLE JOINT			
Brand PN	Global PN	inches	mm	Brand PN	Global PN	inches	mm
B20AA	0368 0305 051	2	50.8	B20SA	0368 0300 051	2	50.8
B25AA	0368 0305 064	2-1/2	63.5	B22SA	0368 0300 057	2-1/4	57.2
B27AA	0368 0300 069	2-3/4	69.9	B25SA	0368 0302 064	2-1/2	63.5
B30AA	0368 0305 076	3	76.2	B27SA	0368 0302 070	2-3/4	69.9
B35AA	0368 0304 076	3-1/2	88.9	B30SA	0368 0301 076	3	76.2
B40AA	0368 0307 102	4	101.6	B35SA	0368 0302 089	3-1/2	88.9
B45AA	0368 0301 114	4-1/2	114.3	B40SA	0368 0303 102	4	101.6
B50AA	0368 0307 127	5	127.0	B45SA	0368 0304 114	4-1/2	114.3
B60AA	0368 0301 152	6	152.4	B50SA	0368 0304 127	5	127.0
				B60SA	0368 0304 152	6	152.4

NORMA Americas Distribution Services

325 West Silverbell Road, Suite 230 | Lake Orion, MI 48359 USA

Tel 1.855.NORMA2U | 1.855.667.6228 | Fax 1.855.804.4646 | Email norma2u@normagroup.com | www.normaAmericasDS.com

